

MediaAccess TG789vn v3

Wireless n VoIP
Ultra Broadband Gateway



TELECOM

DATA

VOICE

VIDEO

Innovation at its Best

The accelerating growth of WAN and LAN traffic is pushing operators to look to higher-speed network technologies to solve the bandwidth crunch.

The TG789vn v3 is a unique future-proof triple-play service gateway allowing VDSL2 connectivity while providing Voice over IP functions for residential users.

A dedicated Gigabit Ethernet WAN port and autoWAN sensing make the TG789vn v3 also the ideal service gateway for deployment in mixed DSL and fiber-based access networks.

In addition to its four Fast Ethernet LAN ports, the TG789vn v3 also offers an IEEE 802.11b/g/n wireless access point for Local Area Network (LAN) access.

Easily Manageable

The TG789vn v3 offers best-in-class TR-069 interoperability with main ACS vendors and even completes the standard with proprietary vendor extensions to increase the range of functionality available.

TR-111 support allows simple management of LAN devices like TR-135 enabled set-top boxes connected to the gateway. TR-104 for VoIP is implemented for the configuration and management of all voice services.

Features at a Glance

- Integrated VDSL2 modem
- 1 GE WAN port with autoWAN sensing™
- 4 FE ports to connect multiple devices, such as PCs, laptops, set top boxes...
- Wireless networking on-board: 802.11b/g/n (2.4 GHz)
- Wi-Fi Protected Setup (WPS™)
- 1 FXO analogue port
- 2 FXS ports
- Media sharing: UPnP A/V and DLNA
- 2 USB 2.0 masters for hard disk, printer, 3G adapter...
- Remotely manageable: TR-069, TR-098, TR-104, TR-111
- Built-in stateful firewall, parental control
- IPv6 ready
- ECO COCv4 compliant



MediaAccess TG789vn v3

Wireless n VoIP

Ultra Broadband Gateway

Home Networking with Easy Installation

Like all Technicolor gateways, the TG789vn v3 interoperates seamlessly with the Technicolor Gateway Setup wizard, making the setup of a wireless home network as easy as clicking a button. No more helpdesk calls are needed, just click and you are ready to go. The Technicolor Gateway Setup wizard performs comprehensive system checks before and during the installation and setup process, and validates all user input to guarantee the end user a secured wireless connection to the Internet.

Furthermore, thanks to the Flexiport feature, the TG789vn v3 automatically detects the Ethernet port where a set-top box is connected. This simplifies the installation process of Internet Protocol Television (IPTV) for end users.

Voice over IP

The TG789vn v3 offers phone POTS ports to accommodate phones and faxes. Once the gateway is registered with a Voice over IP (VoIP) service, regular phone calls can be conducted over the Internet with all the benefits of IP telephony. The gateway offers a wide range of services like caller ID, CLIP, CLIR, call waiting, call forwarding, 3-way conferencing and message waiting notification.

Media Sharing

The TG789vn v3 acts as a central hub for distribution of all content from any device to any device in the home. You can stream music, data, pictures and video from your gateway to devices connected to your wired or wireless home network.

Highest Security

The Technicolor firewall guarantees users the ultimate level in network security. Through integration with NAT, the firewall leverages all the Application Level Gateways (ALGs) provided in the NAT context to minimize undesired service impact. The firewall provides Stateful Packet Inspection (SPI), and an integrated Intrusion Detection and Prevention System (IDS) engine monitors a wide range of attack patterns, and logs potential security breaches to a local cache or remote server.

The TG789vn v3 also supports powerful wireless security mechanisms, such as Wi-Fi Protected Access (WPA2) together with a secure and user-friendly connection and configuration mechanism for wireless clients (WPS).

The support of multiple SSIDs in the gateway enables support for up to four independent wireless access networks. These additional wireless networks allow other wireless users to enjoy the high-performance access without compromising the integrity of the basic network, thus keeping the original network access limited and secure.

MediaAccess TG789vn v3

Wireless n VoIP

Ultra Broadband Gateway

IPv6 Ready

With the approaching IPv4 address pool depletion, our products need to be ready for IPv6. Internet Protocol version 6 is the next generation of Internet technologies aiming to effectively support the ever-expanding Internet usage and functionality, and also to address security concerns that exist in an IPv4 environment.

In this context, the TG789vn v3 has successfully passed the Gold standard IPv6 Ready accreditation.

Technicolor aims to introduce IPv6 as smoothly as possible in customer networks. By providing in-depth knowledge of the networking stack, we guide our customers in their transition from IPv4 to IPv6.

ECO

Technicolor offers its customers ECO-labeled products covering objectives that go beyond those stated in the regulations that all marketed products have to meet.

In addition to carefully selected plastics and packaging to minimize the ecological footprint, the TG789vn v3 benefits from a unique combination of hardware and software features that reduce power consumption substantially. For instance, a button allows the user to disable/enable the wireless access point when its function is not required.

Professional Services

Technicolor offers a wide array of services:

- **Hardware:** Optimize warranty and hardware operations such as repair, logistics, dedicated inventories, recycling, refurbishing, ...
- **Support & Maintenance contracts** providing a technical support line, software support, updates, upgrades, on-site support and training. Dedicated response time can be tailored to fit your organization with BRONZE, SILVER and GOLD agreements.
- **Develop specific software functions, features and GUIs** to create and deploy innovative subscriber services in your market.
- **Technicolor proposes Integration Services** on technologies, products and third-party software to accelerate your project whilst optimizing your time to market. We can also provide resources for project management, engineering and planning, and assist your team with device interoperability tests, proof of concept (POC) and trials.
- **Missions to optimize your Total Cost of Ownership (TCO)** by analyzing your hotline calls and proposing relevant actions to reduce your OPEX budgets.
- **Leveraging its many years of expertise** in creating gateway and set-top box products - with over 200 million devices delivered to diverse markets all around the world - Technicolor has built an experienced and dedicated design team able to propose a great variety of new, innovative design services, ranging from unique product aesthetics to product content.

MediaAccess TG789vn v3

Wireless n VoIP

Ultra Broadband Gateway

Technical Specifications

Hardware Specifications

- Interfaces WAN
 - RJ-11 DSL line port
 - 1 Ethernet WAN 10/100/1000 Base-T port
 - 1 full FXO port
- Interfaces LAN
 - 4-port autosensing 10/100Base-T auto-MDI/MDI-X Ethernet LAN switch
 - 2 FXS POTS ports
 - 2 USB 2.0 hosts/masters
 - Wi-Fi IEEE 802.11b/g/n on-board
- Extras
 - WPS button
 - ECO button
 - Reset button
 - Power button
- Dimensions
 - 218 x 168 x 61 mm (8.6 x 6.6 x 2.4 in.)
- AC Voltage
 - 100-240 VAC (switched mode power supply)
- Temperature
 - 0° - 40° C (32° - 104° F)
- Humidity
 - 20 % to 80 %

DSL Modem Specifications

- Supports multi mode standards
- ADSL compliance
 - ANSI T1.413 Issue 2,
 - ITU-T G.992.1 Annex A, B (G.dmt),
 - ITU-T G.992.2 Annex A, B (G.lite),
 - ITU-T G.994.1 (G.hs)
 - Maximum rate: 8 Mbps for downstream and 1 Mbps for upstream
- ADSL2 compliance
 - ITU-T G.992.3 Annex A, B, L, M (G.dmt.bis),
 - ITU-T G.992.4 Annex A, B, L, M (G.lite.bis)
 - Maximum rate: 12 Mbps for downstream and 1.5 Mbps for upstream
- ADSL2+ compliance
 - ITU-T G.992.5 Annex A, B
 - Maximum rate: 24 Mbps for downstream and 3 Mbps upstream
- VDSL2 compliance
 - Up to 17 MHz profiles (POTS/ISDN)
- Supports Dying Gasp

Management

- Customizable user-friendly GUI via HTTP and HTTPS
- Unified management interface (Mbus)
- AutoWAN sensing™: automatic selection and configuration of WAN interface
- Web services API for remote access (portal, management, diagnostics, applications,...)
- GUI-embedded Easy Setup wizard
- On-demand remote GUI assistance (helpdesk)
- Web-browsing intercept (install / diagnostics)
- Wireless Technicolor Gateway Setup wizard
- TR-069 CPE WAN Management Protocol
 - TR-098 Internet Gateway Device Management
 - TR-104 voice service provisioning and configuration
 - TR-111 home network device management
- TR-064 LAN side configuration
- Zero-touch autoprovisioning

Services

- Printer sharing
- Content sharing
 - Samba file server
 - UPnP A/V™ media server and control point (optional)
 - Certified DLNA® DMS
 - HDD file systems: FAT32, NTFS (optional)
 - Metadata support
 - Remote HDD file access
- 3G USB adapter support
- Dynamic DNS
- URL- and content-based website filtering (optional)

Wireless Performance and Security

- Wi-Fi IEEE 802.11b/g/n access point Wi-Fi CERTIFIED®
- WPA(2)™-Personal, WEP™
- Wi-Fi Multimedia (WMM®)
- Wi-Fi Protected Setup (WPS™)
- Up to 4 BSSIDs (virtual AP) support
- Security and service segregation per SSID
- Dynamic rates switching for optimal wireless rates
- RX/TX switched diversity
- Manual/auto radio channel selection

Security

- Stateful Packet Inspection Firewall (SPIF)
- Customizable firewall security levels
- Intrusion detection and prevention (DoS, SYN Flood, Ping of Death, Fraggle, LAND, Teardrop, ...)
- DeMilitarized Zone (DMZ)
- Multi-level access policy
- "SIM-lock" provider locking

Networking

- Symmetrical NAT with application helpers (ALGs)
- Game and application sharing NAT port maps
- DHCP conditional serving & relay, DNS server & relay
- IGMPv3 proxy
- IGMP snooping
- DHCP spoofing
- Flexiport (automatic selection of Ethernet port bridged IPTV)
- IEEE 802.1q VLAN bridging, multiple bridge instances
- IPv6 ready

Quality of Service (QoS)

- ATM QoS
 - UBR, VBR-nrt, VBR-rt, CBR shaping, queuing and scheduling
 - CLP tagging
- IP QoS
 - Flexible classification (ALG aided)
 - IP rate limiting (two-rate remarking/dropping)
 - DSCP (re) marking
 - TCP ACK optimization
 - Dynamic link fragmentation
 - Per service class connection/resource reservation
- Ethernet QoS
 - Priority or C-VLAN/S-VLAN tagging
 - Switch port queuing and scheduling
- Wireless QoS
 - WMM (BE, BK, VI, VO access categories) queuing and scheduling

MediaAccess TG789vn v3

Wireless n VoIP
Ultra Broadband Gateway



Technical Specifications

Voice over IP Features

- Voice Functionality
 - Signalling: SIP, MGCP (optional), H.323 (optional)
 - Codecs: G.711, G.726, G.729, Wideband (G.722), T.38
 - Echo cancellation: G.168 compliant
 - Comfort Noise Generator (CNG)
 - Flexible telephone number per FXS, including common numbers
- FXO
 - Interoperable with main market softswitches
 - Fully flexible dial plan for PSTN/VoIP outgoing calls
 - Prefix for PSTN/VoIP switch
 - Lifeline backup: manual and automatic PSTN/VoIP
 - Incoming call detection on PSTN
- Supplementary and Advanced Services
 - Call waiting (on call basis)
 - Caller ID
 - Call forwarding (no answer/busy/unconditional)
 - Call transferring
 - Call hold, call return
 - Calling Line Identification Presentation (CLIP)
 - Calling Line Identification Restriction (CLIR)
 - Calling Name Identification Presentation (CNIP)
 - Calling Name Identification Restriction (CNIR)
 - Fax transparency
 - 3-way conference
 - Message Waiting Indicator (MWI)
 - Missed call email
 - Click to dial
 - Warm line
 - Call completion to busy subscriber
 - Forced FXO
 - Abbreviated number
 - Common number in/outgoing call
 - Anonymous Call Rejection (ACR)
 - Distinctive ringing
 - Voice Mail on No Reply (VMNR)
 - Support for secondary outbound proxy
 - DNS NAPTR, DNS SRV

Content of the Box

- Wireless n VoIP Ultra Broadband Gateway
- DSL cable (RJ-11)
- Ethernet cable (RJ-45)
- Power supply unit
- Setup CD and leaflet
- Filter or splitter (optional)



Technicolor TG789vn v3 back panel

TECHNICOLOR WORLDWIDE HEADQUARTERS
1, rue Jeanne d'Arc
92443 Issy-les-Moulineaux France
Tel. : 33 (0) 1 41 86 50 00 - Fax : 33 (0) 1 41 86 58 59

www.technicolor.com

SALES CONTACT

For more information please get in touch with your usual sales representative or use the following email:

EMESalescontact@technicolor.com

APACSalescontact@technicolor.com

NAMSalescontact@technicolor.com

LATAMSalescontact@technicolor.com

technicolor



© Copyright 2012 Technicolor. All rights reserved.
Photos and specifications are subject to change without notice. All trade names referenced are service marks, trademarks, or registered trademarks of their respective companies.
E-DOC-DAT-20100930-0006 v3.0
DS-176-v03-1201