



NLX4000 Elastix®Appliance

Elastix Unified Communications Server



















The Elastix NLX4000 is a powerful communications tool that grows in total synergy with your business. Keeping you in constant contact with your customers, suppliers and employees wherever they are.

Features

- IVR
- Voicemail
- Voicemail to Email
- Dial by name directory
- Music on Hold
- Cascaded calls
- Caller Groups
- New incoming call
- Queues
- Automatic Route Selection
- Call Restrictions
- Call Recordings Detail
- Call Routing
- Auto Fax Detection
- Call filtering
- Call pickup
- and many more.

Take your business to new frontiers

The NLX4000 in conjunction with our Elastix® software becomes a powerful unified communications server that allows your business to grow according to the needs of the market.

The set of features unique to the NLX4000 helps keep your communications always smooth and uninterrupted, thanks to its hardware RAID and easy access to the drives and PCI expansion cards.

Technical Specifications

recrimed specimedions	
	Telephony
Analog Ports (FXO/FXS)	Up to 48 *
Digital Ports	Up to 4 E1/T1/J1*
Extensions (SIP/IAX)	Up to 300 *
Concurrent Calls	Up to120 *
PCI Expansion Slots	2 PCle - easy swap
Operating System	Elastix 32 bits - supports 64 bit
	Hardware
CPU	1.86 GHz Dual Core
RAM	4 GB DDR3
Hard Drive (2nd optional)	500 GB HDD - 2.5"
RAID	Hardware RAID 1
Network Interface	2x Gigabit Ethernet
LCD Display	Front panel
USB Ports	2 on rear panel
	Operation Features
Nominal Power	150 W, efficient PSU
Operation Voltage	100/240v Auto switching
	Physical Features
Height	2.64" (67 mm)
Width	17.32" (440 mm)
Depth	14.65" (372 mm)
Weight	4.3 Kg (9.5 lb)
Metallic Case	1.5U - Rack mountable 19"
oresents a safe estimate on a basic scenario.	

^{*} Represents a safe estimate on a basic scenario Visit http://elx.ec/benchmark for more details.