

GXV3601\_HD

GXV3611\_HD

GXV3651\_FHD

GXV3672\_HD/FHD  
Infrared &  
Weatherproof (IP66)GXV3672\_HD/FHD\_36  
Infrared &  
Weatherproof (IP66)GXV3674\_HD/FHD\_VF  
Vari-focal, Infrared &  
Weatherproof (IP66)GXV3610\_HD  
Infrared &  
Weatherproof (IP66)

GXV3615WP\_HD

GXV3662\_HD/FHD  
Vandal-Resistant &  
Weatherproof (IP66)

## Specifications

Video Compression	H.264, JPEG, Motion JPEG									
ONVIF Compliant	Yes									
Image Sensor	1/3.2" 2 Megapixel CMOS sensor		1/2.5", 5- Megapixel CMOS sensor	1/3", 1.2 Megapixel CMOS, (HD) 1/3", 3.1 Megapixel Progressive Scan CMOS (FHD)	1/3", 1.2 Megapixel CMOS, (HD) 1/3", 3.1 Megapixel Progressive Scan CMOS (FHD)	1/3", 1.2 Megapixel Progressive Scan CMOS (HD) 1/3" 3.1 Megapixel Progressive Scan CMOS (FHD)	1/3" 1.2 Megapixel Progressive Scan CMOS (HD) 1/3" 3.1 Megapixel Progressive Scan CMOS (FHD)	1/3.2", 2-Megapixel CMOS	1/3", 1.2 Megapixel CMOS, 1280H x 960V (HD) 1/3", 3.1 Megapixel CMOS, 2048H x 1536V	
Lens Type	1/3", 2.8 ~ 12 mm, F1.4, Mega Manual – IRIS, (Auto IRIS Lens not supported)		1/3" M12 Mega, f=2.8mm, F2.0	1/2", 4.5 ~ 10mm, Manual – IRIS (Auto IRIS Lens Supported)	1/3" M12 Mega f=8mm, F=1.8	1/3" M12 Mega f= 3.6mm, F=2.0 (HD) 1.8 (FHD)	1/3" 2.8mm-12mm Vari-focal lens with DC-IRIS	1/3" M12 Mega, F=3.6mm, F1.8 (HD)	1/3" M12 Mega, f=4.2mm, F1.8	1/3" 3.3mm-12mm, DC-IRIS
Sensitivity	1.0V/Lux-sec (550nm)		1.4V/Lux-sec (550nm)	5.48V/lux-sec (550nm) (HD) 1.9V/lux-sec (550nm) (FHD)				1.0V/Lux-sec (550nm)	5.48V/lux-sec (550nm) (HD) 1.9V/lux-sec (550nm) (FHD)	
Max Video Resolution	1,600 x 1,200		2,560 x 1,920	1280 x 960 (HD) 2048 x 1536 (FHD)				1,600 x 1,200	1,280 x 960 (HD) 2048 x1536 (FHD)	
Audio Input / Output	3.5mm line – in & line – out, built- in- microphone; SIP/VoIP			N/A	3.5mm line – in & line – out		3.5mm line – out, built- in- microphone; SIP/VoIP	Built - in microphone, Built - in speaker	3.5mm line – in & line – out	
Alarm Input / Output	Alarm Input: Yes – One Interface, Normal Open / Alarm Output: Yes – One Interface, 125VAC/0.5A or 30VAC/2A			N/A					Input: Voltage In <15V; Output: 125VAC/0.5A, 30VDC/2A, Normal Open	
Audio Compression	G.711, G.726		G.711, AAC	N/A	G.711, ACC					
Pre-/ Post Alarm Buffer	24MB			8 MB (HD) 3MB (FHD)				24MB		
Security	Optional Date/Time Watermark, HTTPS, Password									
Network Port	10/100 M port with integrated PoE						WiFi and 10/100 M port with integrated PoE	10/100 M port with integrated PoE		
Multi-streaming- rate	Yes									
SIP/VoIP Support	Yes									
Dimensions	155mm (L) x 68mm (W) x 64mm (H)	138 (D) mm x 86mm (H)	152mm x 68mm x 64mm (L x W x H)	94mm (D) x 230mm (L)		255mm (L) x 104mm (W) x 187mm (H)	120mm (D) x 100mm (H)	90mm (W) x 90mm (H) x 45mm (L)	153mm (D) x 115mm (H)	
Weight	0.6 kg	0.43 kg	0.51 kg	0.52 kg		1.1 kg	0.7 kg	0.25 kg	1.19 kg	
Power Adapter	Output: 12VDC/1A; Input: 100- 240VAC, 50-60Hz									