

# SIP Indoor Intercom with Keypad-Surface Mount

**CyberData**

The IP Endpoint Company

The SIP Indoor Intercom with Keypad-Surface Mount delivers two-way communication and secure access control for your VoIP phone system. These devices are perfect for settings such as commercial/residential facilities, schools and universities, retail establishments, warehouse and manufacturing plants.

CyberData has maintained one of the most comprehensive list of IP PBX servers certified to work with CyberData VoIP Products.

## Features

- TLS 1.2, Enhanced security for IP Endpoints in a local or cloud based environment
- Relay configurable for secure access in all modes
- Security mode allows for up to 500 user codes with configurable times and blacklisting plus extension dialing
- Phone mode allows use as a hands-free phone
- Enhanced acoustic echo canceler
- 12-key keypad with backlight
- Programmable speed dial
- Full-duplex voice operation
- Supports SRST (Survivable Remote Site Telephony) in a Cisco environment
- Streamlined case design
- Network web management and firmware download
- Network adjustable speaker volume
- Concurrent SIP and multicast paging
- Dry relay contact for auxiliary control
- Door closure and tamper alert signal
- Downloadable alert, ringtones and callout messages

## Related Products:



011375 Network Dual Door Strike Relay



011269 Door Strike Intermediate Relay Module



011288 Auxiliary RGB (Multi-Color) Strobe Kit



## Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
Speaker Output	2 Watts Peak Power
On-Board Relay	1A @ 30 VDC
Payload Types	G.711 a-law, G.711μ-law, G.722, and G.729
Network Security	TLS/SSL 1.2
Operating Range	Temperature: -40° C to 55° C (-40° F to 131° F) Humidity: 5-95%, non-condensing
Storage Temperature Storage Altitude	Temperature: -40° C to 70° C (-40° F to 158° F) Up to 15,000 ft. (4573 m)
Dimensions*	6.50 inches [165.0 mm] Length 1.90 inches [48.2 mm] Width 4.53 inches [115.0 mm] Height
Weight Boxed Weight	1.0 lbs. [0.45 kg] 2.0 lbs. [0.90 kg]
Compliance	CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
Warranty	2 Years Limited
Part Number	011113

\*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.

# SIP Indoor Intercom with Keypad-Surface Mount

