

## VOIP GATEWAY MG6016C

GaoKe Communication developed and launched MG600X series to meet the NGN requirement of telecom carrier, service provider and SMB and home users, which including IP Phone, VoIP gateways, Trunking Gateway and NMS, to provide perfect VoIP/FoIP solution. Such series widely support all kinds of protocol and services , performances high-efficiency, safe, high quality voice service. Provide flexible, convenient, abundant voice and wideband data service.

### Front Panel Overview



### Rear Panel Overview



## Specifications

Voice Features	
<b>Analog User</b>	16*FXS
<b>Codec</b>	711A,G.711u,G.723,G.729,AMR_NB,AMR_WB
<b>Protocol</b>	TCP, UDP or TLS
<b>FAX</b>	Transparent, T38, VBD
<b>Voice Functions</b>	Call Forward on Busy Call Forward on No Answer Call Forward Unconditional Caller ID Caller ID on Call Waiting Call Waiting Three- way Calling Ring groups

Firewall & Security	
<b>Firewall Protection</b>	IDS&IPS, Block Ping/ICMP/IDENT, SPI Firewall, Portscan restriction
<b>Access control</b>	Blocking by URL,IP Address,Mac Address, Protocol Type, Port

Data Network	
<b>WAN</b>	1×10/100Mbps Ethernet
<b>LAN</b>	1x10/100Mbps Ethernet
<b>WAN Access Mode</b>	Static IP, PPPoE, DHCP
<b>NAT</b>	ALG, DMZ, PAT

Environmental	
<b>Size</b>	483×239×44mm
<b>Net Weight</b>	<2Kg
<b>Power Supply</b>	AC 220V
<b>Operation Range</b>	0° to 40°C
<b>Humidity</b>	10-90% non-condensing

Management	
<b>Protocol</b>	Telnet, TR069, Web
<b>LED Indications</b>	LED indicators for PWR, REG, ALM RUN and User lines
<b>Control Button</b>	Reset Button