

VOIP GATEWAY MG6032L

GaoKe Communication developed and launched MG600X series to meet the NGN requirement of telecom carrier, service provider and SMB and home users, which including IP Phone, VoIP gateways, Trunking Gateway and NMS, to provide perfect VoIP/FoIP solution. Such series widely support all kinds of protocol and services , performances high-efficiency, safe, high quality voice service. Provide flexible, convenient, abundant voice and wideband data service.

Front Panel Overview



Rear Panel Overview



Specifications

Voice Features	
Analog User	32*FXS
Codec	711A,G.711u,G.723,G.729,AMR_NB,AMR_WB
Protocol	TCP, UDP or TLS
FAX	Transparent, T38, VBD
Voice Functions	Call Forward on Busy Call Forward on No Answer Call Forward Unconditional Caller ID Caller ID on Call Waiting Call Waiting Three- way Calling Ring groups

Firewall & Security	
Firewall Protection	IDS&IPS, Block Ping/ICMP/IDENT, SPI Firewall, Portscan restriction
Access control	Blocking by URL,IP Address,Mac Address, Protocol Type, Port

Data Network	
WAN	1×10/100Mbps Ethernet
LAN	1x10/100Mbps Ethernet
WAN Access Mode	Static IP, PPPoE, DHCP
NAT	ALG, DMZ, PAT

Environmental	
Size	483×239×44mm
Net Weight	<2Kg
Power Supply	AC 220V
Operation Range	0° to 40°C
Humidity	10-90% non-condensing

Management	
Protocol	Telnet, TR069, Web
LED Indications	LED indicators for PWR, REG, ALM RUN and User lines
Control Button	Reset Button