

snom 300

SIP based VoIP Phone

snom OCS
edition

snom
greenVoIP

CTI
inside



- **Two-line display (2x16 characters)**
- **27 keys, 7 LEDs**
- **6 programmable function keys**
- **2x IEEE 802.3 10/100 Mbps switch**
- **4 SIP identities (lines)**
- **Headset connection**
- **SIP RFC3261**
- **Security: SIPS/SRTP, TLS, IEEE 802.1X**
- **STUN, ENUM, NAT, ICE**
- **Codecs: G.711, G.729A, G.723.1, G.722, G.726, GSM 6.10 (full rate)**
- **Power over Ethernet (PoE)**
- **XML driven mini-Browser**
- **Very low energy consumption**

The IP telephone with the latest VoIP technology for the discerning caller! Ideal for ITSPs, offices, and private users.

As the basic model of the snom business telephone family, the SIP telephone **snom 300** fulfils the requirements of VoIP telephony and additionally offers numerous functions that are indispensable for everyday working life. Due to its excellent cost-performance ratio, it is ideal both for ITSP packages/products and for small and medium-sized enterprises, home offices, and private users.

The **snom 300** sets new standards when it comes to user-friendliness: A two-line LCD display shows call infor-

mation, and the menu-driven user interface provides simple feature management.

The **snom 300** is synonymous with effectiveness, time saving and flexibility: It provides all necessary office functionalities, for example choice of outgoing identity, "busy" indication, or picking up calls. Four different identities are possible.

Six user- or administrator-configurable (or carrier-preconfigurable) function keys can easily be allocated to arbitrary menu functions like DND, redirection, deny, etc., or assigned to multiple lines. The **snom 300** comes factory-equipped with two of its six

programmable keys configured as line appearances. You can configure up to all six function keys this way – flexible enough to suit the needs of every user.

Are you afraid of unsolicited eavesdroppers, data theft, or spam calls? Thanks to the **snom 300** you have no need to worry. Due to the security standards SRTP and SIPS, the **snom 300** is just as secure as the business model snom 320. This makes it perfectly suited for use in sensitive environments such as in banks and medical or military establishments.

Technical Data snom 300

GENERAL FEATURES

- **Dimensions:**
approx. 20x18.5x12 cm
- **Weight:** approx. 730 g
- **Safety:** IEC 60950-1:2001,
CB Test Certificate: DE 02011039
- **Certifications:** FCC Class B, CE Mark
- **Power consumption:** 1.7–2.7 watts

CONNECTORS

- **1 x LAN, 1 x PC:** RJ45 (Ethernet)
- **Power:** 5 V DC
- **Ethernet:** 2x IEEE 802.3 10/100 Mbps switch
- **Power over Ethernet:** IEEE 802.3af,
Class 1
- **Handset:** RJ11 connector
- **Headset:** RJ11 connector

USER INTERFACE

- 2x16 character display, backlit
- 27 keys, 6 programmable function keys
with LEDs
- Caller-ID
- Message waiting indication LED
- Address book (100 entries)
- Speed dialing
- Local dial plan
- Number guessing
- Lists of missed, received and dialed calls
(100 entries each)
- Call waiting indication
- Clock, daylight saving, call-timer
- Call blocking (deny list)
- Blocking of anonymous calls
- Handling of 4 simultaneous calls
- Menu-driven user interface
- URL Dialing support
- Do not disturb

- Ring tone selection, import of individual
ring tones
- National language support for selected
languages (NLS)
- Speakerphone (full duplex)
- Auto answer mode
- Keyboard lock

CALL FEATURES

- Hold
- Blind transfer, attended transfer
- Music on hold support (only via PBX)
- Divert
- Conferencing (3-way conference bridge
on phone)
- Call park, call pick-up (only via PBX)
- Call completion
- Client Matter Code (CMC)
- Call waiting/switching between calls
- Redialing
- RTP multicast paging
- Multiple audio device support

WEB SERVER

- Embedded web server HTTP/HTTPS
- Easy configuration of the phone, remote
configuration
- Dial from web interface
- Password protection
- Diagnostics (tracing, logging, syslog)

SECURITY, QUALITY OF SERVICE

- HTTPS (server/client)
- Transport Layer Security (TLS)
- SRTP (RFC3711), SIPS
- RTCP, S-RTCP
- VLAN (IEEE 802.1X)
- LLDP-MED

CODECS, AUDIO

- G.711 A-law, μ -law
- G.729A, G.723.1, G.727
- GSM 6.10 (full rate)
- G.722
- Comfort noise, voice activity detection

SIP

- RFC3261 compliance
- UDP, TCP and TLS
- Digest/basic authentication
- PRACK (RFC3262)
- Error-information support
- Reliability of provisional responses
(RFC3262)
- Early media support
- DNS SRV (RFC3263),
redundant server support
- Offer/answer (RFC3264)
- Message Waiting Indication (RFC3842),
subscription for MWI events (RFC3265)
- Dialog-state monitoring (RFC 4235)
- In-band DTMF/out-of-band DTMF/
SIP INFO DTMF
- STUN client, ICE (NAT traversal)
- ENUM (RFC3261), NAPTR (RFC2915),
rport (RFC3581), REFER (RFC3515)
- Bridged line appearance (BLA)
- Auto provisioning with PnP
- Busy lamp field support (BLF)

INSTALLATION

- Automatic software update
- Automatic settings retrieval
via HTTP/HTTPS/TFTP with authentication
- Installation via web interface
- Static IP provisioning, DHCP
- NTP

snom technology Inc.

18 Commerce Way, Suite 6000
Woburn, MA 01801
tel: +1-781-569-2044
fax: +1-781-569-2045

snom technology AG

Charlottenstraße 68–71
10117 Berlin, Germany
tel: +49 30 39833-0
fax: +49 30 39833-111
sip: info@snom.com
mail: info@snom.com